

## Matt Finish Sealer, 1 & 5 litre



### DESCRIPTION:

A completely natural, matt finish for travertine, limestone, terracotta, quarry tiles, slate, sandstone, marble, concrete, brick and external paving. Delicately enhances colour and texture. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe.

### FEATURES:

- Natural Stone / Travertine
- Limestone / Marble
- Terracotta / Quarry Tiles
- Sandstone / Slate
- Brick / Paving
- Pools / Pool Surrounds
- Interior / Exterior
- Microporous



FM 54357

#### CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK  
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

## PREPERATION

Shake the tin prior to use. Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout.

## APPLICATION

Apply this sealer with a soft cloth or brush allowing at least two hours between coats. More absorbent floors may require further coats and on such floors the product should be generously applied. One hour after application, rub over the surface with a soft fluff free cloth or buffing machine to obtain a uniform finish and remove any material not yet absorbed. This product will dry after about two hours, but will take a further three days to become fully resistant. N.B. The aim is to completely fill the substrate with sealer without over applying it. Do not apply in direct sunlight. The sealer will help to inhibit oil based stains but such spillages should be wiped up immediately. On rougher surfaced floors it may be prudent to use an appropriate surface sealer in conjunction with this sealer.

## COVERAGE

Lower porosity: approximately 1-2 litres per 10m<sup>2</sup>  
Higher porosity: approximately 3-4 litres per 10m<sup>2</sup>

## MAINTENANCE

Routinely sweep the floor and wash with StoneFix Maintenance Liquid. Clean walls and work surfaces with StoneFix Stonewash Cleaner. Avoid using strong detergents and kitchen cleaners to wash surfaces sealed with Colour intensifier.

## PACKAGING & STORAGE

StoneFix Matt Finish sealer is supplied in 1 & 5 litre containers boxed 6 & 4 units respectively. Keep cool and dry.

## HEALTH & SAFETY

Contains: White Spirit (naptha petroleum, hydrodesulphurised heavy (<0.1% benzene).

**FLAMMABLE.** Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

**Harmful:** may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves and goggles. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1300

### VOC STATEMENT

EU Limit value for this product (Cat A/h) 750g/L (2010)  
This product contains max 739g/L VOC



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

## CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK  
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk