

## Colour Intensifying Sealer, 1 & 5 litre



### DESCRIPTION:

Strongly enhances natural colour and appearance of travertine, terracotta, slate, tumbled marble, marble, limestone, sandstone, granite, other types of natural and artificial stone, terrazzo, quarry tiles etc. Provides a matt finish. For use on wall and floor surfaces. Strongly protects against water, oil, grease and dirt. Allows surface to breathe.

### FEATURES:

- Natural Stone / Travertine
- Limestone / Terrazzo
- Terracotta / Quarry Tiles
- Sandstone / Slate
- Brick / Paving
- Pools / Pool Surrounds
- Interior / Exterior
- Microporous



FM 54357

#### CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK  
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

## PREPERATION

This sealer is very difficult to remove once hardened. Do not over apply. The surface to be treated must be completely clean, dry and free from contamination. If necessary, first clean floor with StoneFix Heavy Duty Grime Remover and allow to thoroughly dry.

## APPLICATION

Apply this sealer thinly and uniformly with a cloth, brush or sponge and allow to penetrate for approximately 15-30 minutes before then wiping over with a clean dry fluff-free cloth to remove any excess which may remain on the surface. N.B. The surface must retain a matt finish after treatment. Any excess left on the surface could oxidise to form an unsightly/patchy gloss varnish. For stronger colour enhancement and in the case of more absorbent surfaces, further coats may be applied. Allow at least 30-60 minutes from application of previous coat before applying further coat. Do not apply in direct sunlight or in a temperature exceeding 25oc. Beware of application upon floors with underfloor heating as the product may dry prematurely. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application.

## COVERAGE

Lower porosity: approximately 1-2 litres per 10m<sup>2</sup>  
Higher porosity: approximately 3-4 litres per 10m<sup>2</sup>

## MAINTENANCE

Routinely sweep the floor and wash with StoneFix Maintenance Liquid. Clean walls and work surfaces with StoneFix Stonewash Cleaner. Avoid using strong detergents and kitchen cleaners to wash surfaces sealed with Colour intensifier.

**ATTENTION:** Do not use on polished, glazed, coated or other non-absorbent surfaces. Glass or polished surfaces, plastics or any surface which may be adversely affected by this product must be protected against splashes. Removal may be assisted with white spirit on a clean fluff-free rag.

## PACKAGING & STORAGE

StoneFix Colour Intensifying sealer is supplied in 1 & 5 litre containers boxed 6 & 4 units respectively. Keep cool and dry.

## HEALTH & SAFETY

Contains: White Spirit (naptha petroleum, hydrodesulphurised heavy (<0.1% benzene).

**FLAMMABLE. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.**

**Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.**

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves and goggles. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1993

VOC STATEMENT  
EU Limit value for this product (Cat A/h) 750g/L (2010)  
This Product contains max 749g/l VOC



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

## CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK  
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk