

MPG Sealer, 1 & 5 litre



DESCRIPTION:

A colourless impregnating sealer for mechanically polished porcelain, marble, slate and granite. Provides a completely natural finish on wall and floor surfaces. Easy to apply. Suitable for worktops and fireplaces. Strongly protects against water, oil, grease and dirt.

FEATURES:

- Marble
- Limestone
- Polished Porcelain
- Slate
- Interior / Exterior
- Microporous



FM 54357

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PREPERATION

Ensure surface is clean, dry and free from contamination. If necessary, first clean surfaces with StoneFix Heavy Duty Grime Remover and allow to fully dry. NB: It is important to remove any factory applied sealer or wax from the surface of porcelain before sealing.

APPLICATION

Apply thinly and uniformly using a soft cloth or sponge. **Within 20 minutes, whilst the sealer is still wet on the surface**, buff well using a clean dry cloth or buffing machine. Leave to dry for 4 hours and then on more porous surfaces apply a second coat using the same method. It is important to remember to remove any excess from the surface and buff well between each coat. Do not apply in temperatures exceeding 25°C. Ensure under-floor heating is switched off. Over applied and un-buffed sealer will dry and leave a greasy residue on the surface. To remove, apply white spirit or a little more sealer and then buff immediately. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application. Treated areas should be dry enough to walk on after about 4 hours but will take 3 days to become fully water resistant.

COVERAGE

Approximately 10 – 30m² per litre depending on surface porosity.

MAINTENANCE

Use StoneFix Maintenance Liquid for floors and StoneFix Stonewash Cleaner for walls. For stubborn surface marks use StoneFix Heavy Duty Grime Remover, in which case you may need to re-seal treated areas. Do not use strong bleach cleaners for routine maintenance.

ATTENTION: Do not use on polished, glazed, coated or other non-absorbent surfaces. Glass or polished surfaces, plastics or any surface which may be adversely affected by this product must be protected against splashes. Removal may be assisted with white spirit on a clean fluff-free rag.

PACKAGING & STORAGE

StoneFix MPG Sealer is supplied in 1 & 5 litre containers boxed 6 & 4 units respectively. Keep cool and dry.

HEALTH & SAFETY

Contains: Naphtha (petroleum), hydrodesulfurized heavy: low boiling point (white spirit). **FLAMMABLE. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.**

Keep away from food, drink and animal feeding stuffs. Keep out of reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1300

VOC STATEMENT
EU Limit value for this product (Cat A/h) 750g/L (2010)
This product contains max 739g/L VOC



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk