

Stone Oil Sealer, 1 & 5 litre



DESCRIPTION:

Easy to apply oil based impregnating sealer ideal for porous stone and low porosity terracotta. Enhances the colour and texture of floors and offers good mechanical strength once cured.

FEATURES:

- Porous stone
- Limestone
- Sandstone
- Terracotta
- Interior / Exterior
- Impregnating Sealer



FM 54357

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PREPERATION

Shake well. Ensure surface to be treated is completely dry and free from contaminants which may prevent Stone Oil from properly curing.

APPLICATION

Apply by brush or clean fluff-free cloth depending on the required application. Please note more porous floors may require more than one application, remove any excess sealer that has not been fully absorbed within 1 hour. Leave to cure for a minimum of 24 hours before finishing the surface with **StoneFix Matt Finish Sealer, StoneFix Colour Intensifying Sealer or StoneFix Satin Finish Sealer.**

IMPORTANT

If using this product outside finish with either a coat of StoneFix Matt Finish Sealer or StoneFix Colour Intensifying Sealer to offer extra protection.

COVERAGE

Approximately 1-2 litres per 10m².

MAINTENANCE

Routinely sweep the surfaces. Use Stonefix Maintenance Liquid to clean and protect surfaces. In areas where the seal becomes worn, apply more finishing sealer. At some stage, complete renovation of the seal may be desired. In this case use StoneFix Heavy Duty Grime Remover to strip the surface before re-applying more of the finishing seal.

ATTENTION

Allow good ventilation during application. StoneFix Stone Oil may cure more rapidly in dry or higher temperature conditions. Avoid working in direct sunlight; rapid oxidisation may inhibit effectiveness of the product. Do not allow the Oil to dry on the surface. Used cloths should be thoroughly washed in soapy water or burnt after use as they may spontaneously combust.

PACKAGING & STORAGE

StoneFix Stone Oil is supplied in 1 & 5 litre containers boxed 6 & 4 units respectively. Keep cool and dry.

HEALTH & SAFETY

Contains: White Spirit (naphtha petroleum, hydrodesulphurised heavy (<0.1% benzene). **FLAMMABLE. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful : may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.**

Keep away from food, drink and animal feeding stuffs.

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1300

VOC STATEMENT
EU Limit value for this product (Cat A/h) 750g/L (2010)
This product contains max 419g/L VOC



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk