

Satin Finish Sealer, 1 & 5 litre



DESCRIPTION:

Easy to apply, low maintenance self-shine satin finish acrylic sealer. Enhances colour and texture. Protects against staining and stubborn dirt. Easy to maintain. May be used on travertine, limestone, sandstone, slate, un-polished marble, terracotta, quarry, bricks, terrazzo and concrete. Suitable for domestic and commercial use.

FEATURES:

- Natural Stone / Travertine
- Limestone / Sandstone
- Terracotta / Terrazzo
- Brick / Slate
- Un-Polished Marble
- Quarry Tiles
- Internal Use
- Surface Seal



FM 54357

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PREPARATION

Ensure surface to be treated is completely clean, dry (min 24hrs). Any retained moisture may cause the StoneFix Satin Finish Sealer to dry opaque or prevent the seal from reaching full hardness.

APPLICATION

Rough cut, textured or riven surfaces Use a sponge or paint brush, apply a thin coat evenly in one direction. Do not rub or buff. Allow to dry (1 hr). Apply until an evenly thin film is created. (avg. 3 times). For a higher sheen further coats should be applied at right angles to the previous (max.6).

Honed and smooth surfaces apply using a J cloth saturated with the solution. Pour contents into a separate container. Dip cloth into the solution and wring out. Fold the cloth and apply a thin coat evenly to the surface without rubbing. Apply until an evenly thin film is created (avg. 3 times). Allow to dry (1 hr). For a higher sheen further coats should be applied at right angles to the first (max.6).

Do not over apply as too many coats may cause unsightly build up and/or reduce the efficiency of the product. Hardens after about an hour but will take a further three days to achieve full hardness and become fully water resistant. If in doubt, experiment on spare tiles to establish the correct method of application and optimum number of coats before general use.

COVERAGE

Approximately 15 – 30m² per litre per coat dependant on surface porosity.

MAINTENANCE

Routinely sweep the floor. Use StoneFix Maintenance Liquid to clean and protect treated surfaces. In areas where the seal becomes worn, apply more sealer. At some stage, complete renovation of the seal may be desired. In this case use StoneFix Heavy Duty Grime Remover to strip the original seal before re-sealing.

ATTENTION

Avoid shaking the bottle prior to use. Frothing of liquid may lead to an inconsistent finish. Store in a frost proof place. Do not use below freezing. StoneFix satin finish sealer may not properly adhere to highly vitrified quarry tiles or ceramics. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity floor materials such as terracotta and limestone, a suitable impregnating sealer may be required prior to use of StoneFix Satin Finish Sealer.

PACKAGING & STORAGE

StoneFix Satin Finish Sealer is supplied in 1 & 5 litre containers boxed 6 & 4 units respectively. Keep cool and dry.

HEALTH & SAFETY

Keep out of reach of children.

After contact with skin, wash with soap and water.

Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk