

Paving Sealer, 5 & 25 litre



DESCRIPTION:

StoneFix Paving Sealer is a high performance ready to use eco-friendly sealer that helps protect against staining. Strongly repels water, oil and grease while still allowing the surface to breath. Enhances the present colour and greatly extends the life span of paving patio, driveways and paths.

FEATURES:

- Natural Stone
- Concrete
- Protects from Water Penetration
- Enhances Colour
- Block Paving
- Eco friendly / No VOCs
- Oil Resistant
- Anti-stain / Watermark Proof



FM 54357

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PLEASE NOTE

DO NOT apply if frost is forecast within 24 hours, in wet conditions, in temperatures below 5°C or above 25°C, to areas in direct sunlight or to substrates that are hot.

Do not apply to non-porous surfaces. Keep children and pets away from treated areas until fully cured. Do not allow any run off to contaminate drains, waterways or plants; it is the user's responsibility to determine suitability for use.

If in doubt please speak to our technical department.

PREPARATION

Remove any moss or lichen that may be present. For best results use StoneFix Mould Buster, refer to data sheet for application instructions. Wash all debris away and ensure the surface is dry and free from oil, grease, dust and loose material that may hinder adhesion.

APPLICATION

Paving Sealer is ready to use and does not require diluting. **SHAKE WELL BEFORE USE.** Ensure that the surface is completely dry. Apply using either a brush, roller or sponge, ensuring that no pooling or ponding occurs. We recommend a two coat application allowing 3-4 hours between coats. Application temperature should be above 5°C and below 30°C.

COVERAGE

Approximately 5-7m² per Litre.

Coverage is dependent on the application technique and substrate these figures are therefore only a guide.

PACKAGING & STORAGE

StoneFix Paving Sealer is supplied in 5 & 25 litre containers. When stored unopened in a cool dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

HEALTH & SAFETY INSTRUCTIONS

- Product presents a low hazard in correct use.
- Keep out of reach of children.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
- If swallowed, seek medical advice immediately and show this container or label.

For further information, please request the material safety data sheet for this product.

QUALITY CONTROL

All StoneFix products are factory blended, tested and packaged to quality control procedure in accordance with BS EN ISO 9001 series.

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk