

Mould Buster, 5 litre



DESCRIPTION:

StoneFix Mould Buster is a powerful, non-toxic cleaning agent based on organic acids which removes all types of moss, moulds, algae and lichens. Used for removing all types of algae, moss & lichens from natural stone, concrete, block paving.

FEATURES:

- Natural Stone
- Concrete
- Powerful Cleaning Agent
- Enhances Colour
- Block Paving
- Eco-friendly / No VOCs
- Non-toxic / Safe for Pets and Wildlife
- Anti-stain / Watermark Proof



FM 54357

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PLEASE NOTE

DO NOT apply if frost is forecast within 24 hours, in wet conditions, in temperatures below 5°C or above 25°C, to areas in direct sunlight or to substrates that are hot.

Mould buster will scorch foliage where it makes contact; however, small amounts of runoff should not harm roots. Take care near fish ponds, a few drops entering water will not harm fish or pond life but try to avoid this happening.

Mould buster may attack marble and some metals.

Keep children and pets away from treated areas until fully cured. Do not allow any run off to contaminate drains, waterways or plants, it is the users responsibility to determine suitability for use. If in doubt please speak to our technical department.

APPLICATION

Ideally use when rain is not imminent.

Dilute 1 part Mould Buster to 3 parts water.

Apply using either paint roller or brush for large areas a spray or watering can is suitable.

Apply evenly to the surface to be treated. Mould eradication will begin as the product dries – leave for a few days to reach full strength.

For moss and lichen may need further applications. Any residue should weather away over a period of time.

Note: For a new clean finish complete process with a pressure wash clean down, followed by application of StoneFix Paving Sealer.

COVERAGE

5 LTR diluted as per directions will cover up to 120 sqm dependant on porosity of the surface.

Coverage is dependent on the application technique and substrate these figures are therefore only a guide.

PACKAGING & STORAGE

StoneFix Paving Sealer is supplied in 5 litre containers. When stored unopened in a cool dry place at temperatures above 5°C, shelf life is 24 months from date of manufacture. Keep away from direct sunlight, animals, and children and protect from frost.

HEALTH & SAFETY INSTRUCTIONS



- Contains organic acid. Irritant.
- Keep out of reach of animals & children.
- Avoid contact with skin and eyes.
- Do not breathe concentrated vapour.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
- If swallowed, seek medical advice immediately and show this container or label.

For further information, please request the material safety data sheet for this product.

QUALITY CONTROL

All StoneFix products are factory blended, tested and packaged to quality control procedure in accordance with BS EN ISO 9001 series.

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk